



## Features

- Cost effective
- Low power consumption
- IP65 rated front bezel
- Resistive touch screen

## Specifications

Display & Touch Screen	Display Size	15" TFT-LCD
	Max. Resolution	1024 x 768
	Luminance	420 (cd/m <sup>2</sup> )
	Contrast	800 : 1
	Max. Color	16.2M
	View Angle (H/V)	160°/160°
	Backlight Lifetime	30,000 hrs
	Touch Type	Resistive capacitive
	Touch Interface	USB
	Light Transmission	79 %
	Point of touch	1
	I/O Interface	USB 3.0
USB 2.0		2 at rear and 1 at front side with cover
RS-232/422/485 Selectable under BIOS		1
RS-232		1
LAN		2x GbE
Additional Graphics		1x DVI-D and VGA
Audio		MIC in/Line in/Line out phone jack
Digital I/O		None
Power Connector		DC 3 pin terminal block
Power Button		Rock switch
Mechanical	Dimensions	410 x 335 x 79 mm
	Net Weight	7.9kg
System	Processor	Intel® Celeron™ Processor J1900 2.0 GHz
	Memory	2x DDR3L SO-DIMM, up to 8GB, default 4GB
	Thermal Design	Fanless
	Membrane Control	None
	Built-in Speaker/MIC	None
Expansion	Internal Expansion Bus	1x Mini PCI-E(x1) [full/half-size] 1x Mini PCI-E(x1) [half-size]
	Expansion Slot	None
	Wireless	Optional
Storage Space	HDD	1x 2.5" SATA 64GB SSD as default
	Removable	None
Power	Power Input Range	12V/ 24V DC

Construction	Chassis Material	SGCC
	Color (Front/Back)	Black/Black
	IP Rating	Front IP65 / Back IP30
	Mounting	Panel mount and VEAS 75x75mm/ 100x100mm
Environment	Operating Temperature	0°C ~ 50°C(SSD)
	Storage Temperature	-20°C ~ 60°C
	Storage Humidity	10%~90% (non-condensing)
	Certification	CE/FCC class B and LVD
	Operating System Support	Windows 7 Pro/ WES7 and 8/ Windows 8.1/ Win10/ Linux Kernel 3.x

## Ordering Information

ICC-1503DC-RE	15" Fanless Design Panel PC with M1805, Intel® Celeron™ Processor J1900 2.0 GHz, 4GB DDR3L SO-DIMM, 64G SSD, Resistive touch
---------------	--

## Dimensions

ICC1503-DC-RE  
ICC1503-DC-RE-W10

